




TYPE 1



TYPE 2



PCB LAYOUT

SPECIFICATIONS

1. Current Rating: 3A AC, DC
2. Voltage Rating: 250V AC, DC
3. Temperature Range: -25°C ~ +85°C
4. Contact Resistance: 20mΩ Max
5. Insulation Resistance: 1000MΩ Min
6. Withstanding Voltage: 1000V AC/minute
7. Material: Wafer Nylon66, UL94V-0  
PIN Brass Tin-plated

编号	尺寸 (mm)	
	A	B
A2501-02AW	2.50	7.50
A2501-03AW	5.00	10.00
A2501-04AW	7.50	12.50
A2501-05AW	10.00	15.00
A2501-06AW	12.50	17.50
A2501-07AW	15.00	20.00
A2501-08AW	17.50	22.50
A2501-09AW	20.00	25.00
A2501-10AW	22.50	27.50
A2501-11AW	25.00	30.00
A2501-12AW	27.50	32.50
A2501-20AW	47.50	52.50

制图 DRAWN	零件名称 DESCRIPTION	日期 DATE	GENERAL TOLERANCE	材料 MATERIAL	品牌 Brand	料号 PART NO.	规格 SPEC	版本 REV.
			X.±0.25	X.±2"	Jone	JS25T-S**XH**00		A
			X.±0.20	.X"±1"	Meind	XH 2.5mm 插件弯针		1/1
			.XX±0.15	.XX"±0.5"	批准 APPROVAL	客户料号 CUST. NO.		
			.XXX±0.10	.XXX"±0.5"	日期 DATE	比例 SCALE		
				单位 UNITS	2018.6.16	1:1		

深圳市钜硕电子有限公司  
SHENZHEN JUSHUO ELECTRONIC CO., LTD